



Orthorectified and Principal Component RADARSAT-1 Image Dataset for NTS 84E, Alberta

Orthorectified and Principal Component RADARSAT-1 Image Dataset for NTS 84E, Alberta

Shilong Mei

Alberta Geological Survey

February 2004

©Her Majesty the Queen in Right of Alberta, 2004

The Alberta Energy and Utilities Board/Alberta Geological Survey (EUB/AGS) and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness or reliability of this publication. Any software supplied with this publication is subject to its license conditions. The data are supplied on the understanding that they are for the sole use of the licensee, and will not be redistributed in any form, in whole or in part, to third parties. Any references to proprietary software in the documentation and/or any use of proprietary data formats in this release do not constitute endorsement by the EUB/AGS of any manufacturer's product.

When using information from this publication in other publications or presentations, due acknowledgment should be given to the EUB/AGS. The following reference format is recommended:

Mei, Shilong (2004): Orthorectified and principal component RADARSAT-1 image dataset for NTS 84E, Alberta; Alberta Energy and Utilities Board, EUB/AGS Geo-Note 2003-24.

Published February 2004 by:

Alberta Energy and Utilities Board
Alberta Geological Survey
4th Floor, Twin Atria Building
4999 – 98th Avenue
Edmonton, Alberta
T6B 2X3
Canada

Tel: (780) 422-3767 (Information Sales)

Fax: (780) 422-1918

E-mail: EUB.AGS-Infosales@gov.ab.ca

Web site: www.ags.gov.ab.ca

Contents

Acknowledgments	iv
Abstract	v
1 Introduction	1
2 RADARSAT-1 Standard Beam Mode Images	1
3 Processes for Acquisition of the Orthorectified and Principal Component RADARSAT-1 Images for NTS 84E	3
3.1 Original RADARSAT-1 Standard Beam Mode Images	3
3.2 Orthorectification Process	7
3.3 Mosaic (Tiling) Process	8
3.4 Principal Component Analysis	9
3.5 Additional Resampled Images and Maps.....	10
4 Conclusion	10
5 References	10

Tables

Table 1 List of the Path Images that Overlay NTS 84E	5
--	---

Figures

Figure 1 RADARSAT-1 beam modes	2
Figure 2 Coverage sizes and resolutions of RADARSAT-1 beam modes	2
Figure 3 Multi-beam configuration of RADARSAT-1 S1 and S7 ascending/descending imagery.....	3
Figure 4 One of the original SGF scene images used for tiling the NTS 84E dataset: scene MO200868 of Standard Beam Mode 7 descending	4
Figure 5 The scenes overlaying NTS 84E.....	6
Figure 6 One of the orthorectified scene images used for tiling the NTS 84E dataset: scene MO200868 of Standard Beam Mode 7 descending	7
Figure 7 Pseudocolour composite of orthorectified NTS 84E image dataset of Standard Beam Mode S1/S7 ascending/descending beam positions	8
Figure 8 Pseudocolour composite of NTS 84E image dataset of principal component PC1, PC2, PC3 and PC4	9
Figure 9 RADARSAT-1 Standard Beam 1 Ascending Image for Chinchaga River (NTS 84E).....	11
Figure 10 RADARSAT-1 Standard Beam 1 Descending Image for Chinchaga River (NTS 84E)	12
Figure 11 RADARSAT-1 Standard Beam 7 Ascending Image for Chinchaga River (NTS 84E).....	13
Figure 12 RADARSAT-1 Standard Beam 7 Descending Image for Chinchaga River (NTS 84E).....	14
Figure 13 RADARSAT-1 Principal Component 1 Image for Chinchaga River (NTS 84E)	15
Figure 14 RADARSAT-1 Principal Component 2 Image for Chinchaga River (NTS 84E)	16
Figure 15 RADARSAT-1 Principal Component 3 Image for Chinchaga River (NTS 84E)	17
Figure 16 RADARSAT-1 Principal Component 4 Image for Chinchaga River (NTS 84E).....	18

Acknowledgments

The author wishes to acknowledge the support of the Department of Sustainable Development, Government of Alberta, for the acquisition of the RADARSAT-1 path imagery. Ken Dutchak, Gerry Mitchell and Eric Grunsky provided information on processing the RADARSAT-1 imagery. RADARSAT International (RSI) granted permission for using their figures in RADARSAT Geology Handbook (1997) and the online version of RADARSAT Illuminated (1999) to produce Figure 1 and Figure 2 herein. Alberta Geological Survey colleagues Reg Olson, Joan Waters and Gisela Hippolt-Squair are thanked for their beneficial reviews.

Abstract

This report details the acquisition, characteristics and processing of the orthorectified and principal component RADARSAT-1 images for NTS map area 84E by the Alberta Geological Survey (AGS). The acquisition of the original RADARSAT-1 scene imagery was made through a Provincial Partnership Memorandum of Understanding. Original RADARSAT-1 path images (SGF) have been purchased by Alberta Sustainable Resource Development (SRD) from RADARSAT International (RSI) and then made available to AGS, based on an agreement that AGS would pay for orthorectification of the original RADARSAT-1 imagery in exchange for obtaining the value-added imagery for public distribution.

This resulted in acquisition of coverage for all of northern Alberta (north of 55 degrees north latitude) for Standard Beam Modes S1 and S7 in both ascending and descending look directions. This imagery is available at a nominal resolution of 12.5 m. Two hundred and fifty scenes have been orthorectified and, in total, cover northern Alberta (north of 55 degrees north latitude) in the four beam positions. They were tiled to 25 1:250 000 scale NTS map areas. The image file for each NTS map area contains four layers to accommodate four images from the four beam positions. These four layers were then used for principal component analysis to produce an image file for each NTS map area containing four layers holding PC1, PC2, PC3 and PC4 images. The orthorectified and principal component RADARSAT-1 dataset for NTS map area 84E is one of the 25 NTS-tiled products to be delivered to the public by AGS. It will permit users to further process and interpret the RADARSAT-1 data to obtain geoscience, environmental, forestry or other information.

1 Introduction

The Government of Alberta participated in a RADARSAT-1 pre-launch agreement that permitted the acquisition of radar imagery at a significantly reduced price. The acquisition of the RADARSAT-1 imagery was made through a Provincial Partnership Memorandum of Understanding that offered participating provinces a price of \$609 CDN per scene. This agreement tested the application of RADARSAT-1 satellite imagery for agricultural, mapping and natural resources management. Alberta Sustainable Resource Development (SRD) and the Alberta Geological Survey (AGS) participated in this agreement, and they agreed to a satellite image acquisition plan in 1999. The funding of the original RADARSAT-1 path images (SGF) was covered and managed by SRD, and it was agreed AGS would pay for orthorectification of the original RADARSAT-1 imagery in exchange for its use. AGS agreed to provide a complete set of orthorectified imagery to SRD in return. The RADARSAT-1 imagery was obtained from September to December 1999. A total of 274 scenes of RADARSAT-1 standard beam modes S1 and S7 were captured for both ascending and descending passes, covering all of northern Alberta (north of 55 degrees north latitude). This number was mistakenly reported as 280 scenes in previous reports (Grunsky, 2002a, 2002b, 2002c), due to 6 duplicate records of scenes that were found afterwards. Two hundred and fifty of the 274 scenes were orthorectified and then tiled to 25 NTS map areas (Grunsky, 2002a). The other 24 scenes were not orthorectified because they are peripheral complementary images. The image file for each NTS map area contains four layers to accommodate four images from the four beam positions. These four layers were then used for principal component analysis (PCA) to produce an image file for each NTS map area, which contains four layers with PC1, PC2, PC3 and PC4 images. Each of the four principal components of the 25 tiled NTS areas was then assembled to produce the northern Alberta mosaic of principal component images (Grunsky, 2002b). All of these value-added images are made available to the public by AGS. A detailed documentation of the acquisition and availability of these images is provided by Grunsky (2002a).

The RADARSAT-1 satellite is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals it receives back. It differs from optical sensors, such as LANDSAT TM and SPOT, which are referred to as passive systems. Since the optical sensors collect data at frequencies of visible and infrared, they rely on sunlight reflected off the Earth and, as a result, are unable to collect data in darkness or poor atmospheric conditions, such as cloud cover, fog, dust, hail or smoke. RADARSAT-1's longer microwave wavelength is better suited for atmospheric penetration and can collect data regardless of the Earth's atmospheric conditions. The radar backscatter qualities are directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are complementary to optical satellite images. In addition, radar can acquire multiple images to provide stereoscopic viewing.

The imagery obtained by AGS has great potential in geological studies when combined with other satellite images and existing geological data. September to December 1999, when the imagery was obtained, was a dry autumn and, thus, provided ideal conditions of no deciduous foliage and no snow. The four combinations of varying incidence angles and look directions provided four additional dimensions for highlighting differences in geomorphology, surficial and structural features and drainage. For example, Grunsky (2002c) applied the principal component images for land cover and terrain mapping, and Paganelli et al. (2003) used them for structural mapping in a portion of the northern Buffalo Head Hills area. This report describes the acquisition, characteristics and processing of the orthorectified and principal component RADARSAT-1 image dataset for NTS 84E.

2 RADARSAT-1 Standard Beam Mode Images

RADARSAT-1 was launched on November 4, 1995, as a result of a joint venture between the Canadian government, private industry and NASA (RADARSAT International (RSI), 1999). As Canada's first

Earth observation satellite, and the world's first operationally-oriented radar sensor, it provides complete global coverage with the satellite's orbit repeated every 24 days. The Arctic is imaged daily, whereas equatorial areas achieve complete coverage approximately every five days. It differs from research-oriented radar sensors, such as ERS and JERS-1, as it is the first radar sensor totally dedicated to operational applications, and it offers a variety of beam modes to meet requirements for the particular application at hand. It uses a single frequency C-Band (5.3 Ghz frequency or 5.6 cm wavelength) and has the ability to send and receive this microwave energy at a number of spatial resolutions and different incidence angles over a 500-kilometre range. RADARSAT-1's side-looking geometry greatly enhances subtle topographic features that aid in the interpretation of lineaments (RADARSAT International (RSI), 1997). RADARSAT-1 offers 35 beam positions with a viewing angle range of 10 to 60 degrees (Figure 1). The spatial resolution can vary from 8 m to 100 m (Figure 2). As a result, the RADARSAT-1 satellite is programmable so various beam modes and resolutions can be changed according to requirements.




Figure 1. RADARSAT-1 beam modes (used with permission from RADARSAT International (RSI), 1997).




Figure 2. Coverage sizes and resolutions of RADARSAT-1 beam modes (modified after RADARSAT International (RSI), 1999).

The orthorectified and principal component RADARSAT-1 image datasets for NTS 84E contain images from two beam modes and four beam positions: Standard Beam Mode 1 ascending, Standard Beam Mode 1 descending, Standard Beam Mode 7 ascending and Standard Beam Mode 7 descending (Figure 3). It also includes four principal component images (PC1, PC2, PC3 and PC4) derived from them.




Figure 3. Multi-beam configuration of RADARSAT-1 S1 and S7 ascending/descending imagery (after Grunsky, 2002a).

3 Processes for Acquisition of the Orthorectified and Principal Component RADARSAT-1 Images for NTS 84E

The RADARSAT-1 image orthorectification, mosaic and principal component analysis were carried out by Resource GIS and Imaging Ltd. (RGI) using processing methods and software developed by RGI and proprietary to RGI. Their software and processes run within the ER Mapper processing environment.

The processes for producing the orthorectified and principal component RADARSAT-1 Image dataset for NTS 84E are:

- acquisition of the original RADARSAT-1 Standard Beam Mode path images
- orthorectification of the path images
- mosaicking of the orthorectified scene images to NTS map areas; and
- principal component analysis of the tiled NTS map area images.

Following are detailed descriptions of the original input data and steps to produce the orthorectified and principal component RADARSAT-1 images for NTS 84E.

3.1 Original RADARSAT-1 Standard Beam Mode Images

The original RADARSAT-1 image data are the path images (SGF) and have been converted to ground range and are multi-look processed. Each Standard Beam image is a composite of four looks. This composite increases the signal-to-noise ratio at the expense of the spatial resolution. The imagery is provided at a nominal resolution of 12.5 m (close to the single look spatial resolution), although the true spatial resolution of the averaged four-look image is closer to 25 m. The image is calibrated, but remains

oriented in the direction of the orbit path. The image is sampled in unsigned, 16-bit integer format and written in Committee of Earth Observation Satellites (CEOS) standard format. The projection is in UTM zone 11 or 12 with an ellipsoid of WGS84. Figure 4 shows an example of the original path images used for tiling the NTS 84E dataset. Table 1 lists the scenes that overlay the NTS 84E area. Figure 5 shows the spatial locations of the scenes overlaying NTS 84E. Many of these scenes were used for producing the NTS 84E orthorectified and principal component image datasets included on the CD.




Figure 4. One of the original SGF scene images used for tiling the NTS 84E dataset: scene MO200868 of Standard Beam Mode 7 descending. RADARSAT data © Canadian Space Agency/Agence spatiale canadienne 1999, processed and distributed by RADARSAT International.

Table 1. List of the Path Images that Overlay NTS 84E

Scene ID	Beam	Path	UL_LAT	UL_LONG	UR_LAT	UR_LONG	LR_LAT	LR_LONG	LL_LAT	LL_LONG
M0198315	S1	ASC	58:11:44.11N	118:49:44.68W	58:26:39.88N	116:55:57.53W	57:31:49.62N	116:31:31.87W	57:17:08.31N	118:22:24.26W
M0198314	S1	ASC	57:22:32.30N	118:25:03.84W	57:37:14.97N	116:33:54.79W	56:42:21.75N	116:10:18.18W	56:27:52.59N	117:58:40.93W
M0196327	S1	ASC	58:15:41.28N	119:54:38.73W	58:30:38.22N	118:00:36.97W	57:35:48.16N	117:36:07.37W	57:21:05.76N	119:27:13.61W
M0196326	S1	ASC	57:26:27.61N	119:29:52.78W	57:41:11.37N	117:38:29.91W	56:46:18.33N	117:14:49.69W	56:31:48.15N	119:03:25.55W
M0195859	S1	ASC	58:09:57.41N	120:54:13.44W	58:24:52.96N	119:00:30.28W	57:30:02.63N	118:36:06.35W	57:15:21.50N	120:26:55.00W
M0195858	S1	ASC	57:20:45.14N	120:29:34.33W	57:35:27.63N	118:38:29.03W	56:40:34.33N	118:14:54.03W	56:26:05.33N	120:03:13.25W
M0196923	S1	DES	57:45:46.19N	120:11:32.13W	57:31:08.11N	118:20:33.40W	56:36:28.93N	118:47:02.55W	56:50:53.49N	120:35:14.46W
M0196922	S1	DES	58:35:08.43N	119:49:25.09W	58:20:17.24N	117:55:47.78W	57:25:41.99N	118:23:14.95W	57:40:18.71N	120:13:56.94W
M0196561	S1	DES	57:44:16.66N	119:08:33.68W	57:29:39.16N	117:17:40.81W	56:34:59.86N	117:44:08.13W	56:49:23.87N	119:32:14.49W
M0196560	S1	DES	58:33:38.97N	118:46:28.11W	58:18:48.40N	116:52:56.92W	57:24:12.63N	117:20:22.32W	57:38:48.76N	119:10:58.48W
M0196424	S1	DES	57:48:05.99N	121:13:38.38W	57:33:27.10N	119:22:30.51W	56:45:29.46N	119:45:50.87W	56:59:56.38N	121:34:31.45W
M0196423	S1	DES	58:37:28.28N	120:51:29.03W	58:22:36.25N	118:57:42.25W	57:28:01.17N	119:25:12.27W	57:42:38.67N	121:16:03.25W
M0196089	S1	DES	57:50:20.28N	118:03:41.31W	57:35:41.20N	116:12:28.35W	56:41:02.30N	116:39:02.41W	56:55:27.77N	118:27:27.79W
M0198984	S7	ASC	58:13:03.62N	118:50:19.83W	58:21:26.45N	116:56:39.70W	57:26:48.71N	116:43:33.70W	57:18:25.45N	118:34:22.12W
M0198983	S7	ASC	57:23:37.78N	118:35:53.53W	57:32:01.01N	116:44:49.14W	56:37:23.27N	116:31:56.96W	56:28:59.29N	118:20:18.59W
M0196156	S7	ASC	58:24:57.07N	120:00:12.19W	58:33:19.40N	118:05:55.14W	57:38:42.68N	117:52:46.43W	57:30:19.99N	119:44:09.61W
M0196155	S7	ASC	57:35:35.26N	119:45:42.38W	57:43:57.92N	117:54:02.88W	56:49:19.58N	117:41:07.83W	56:40:56.23N	119:30:02.48W
M0195842	S7	ASC	58:16:14.30N	121:00:06.54W	58:24:36.88N	119:06:17.78W	57:34:18.19N	118:54:12.63W	57:25:55.24N	120:45:22.37W
M0195841	S7	ASC	57:31:08.10N	120:46:54.27W	57:39:30.96N	118:55:29.23W	56:44:53.24N	118:42:35.16W	56:36:29.66N	120:31:16.19W
M0200868	S7	DES	57:47:29.32N	119:54:07.65W	57:39:10.63N	118:02:37.50W	56:44:32.69N	118:18:14.45W	56:52:52.13N	120:06:59.67W
M0200867	S7	DES	58:36:55.72N	119:42:17.40W	58:28:37.43N	117:48:09.26W	57:33:59.82N	118:04:09.27W	57:42:18.54N	119:55:23.34W
M0199672	S7	DES	57:47:24.24N	118:52:03.55W	57:39:05.35N	117:00:33.72W	56:44:26.44N	117:16:11.24W	56:52:46.07N	119:04:56.11W
M0199671	S7	DES	58:36:41.26N	118:40:15.34W	58:28:22.70N	116:46:07.29W	57:33:45.72N	117:02:07.37W	57:42:04.71N	118:53:21.41W
M0198791	S7	DES	57:44:27.11N	120:58:29.21W	57:36:08.32N	119:07:09.09W	56:41:29.39N	119:22:45.10W	56:49:48.95N	121:11:20.80W
M0198790	S7	DES	58:33:51.69N	120:46:40.54W	58:25:33.27N	118:52:42.39W	57:30:56.24N	119:08:40.90W	57:39:15.11N	120:59:45.60W








Figure 5. The scenes overlaying NTS 84E.

3.2 Orthorectification Process

The original RADARSAT-1 path images are orthorectified by RGI contracted by AGS. The individual orthorectified RADARSAT-1 images have no filtering nor any radiometric processing applied to them. Radiometrically they are identical to the original images. Orthorectification is performed using digital elevation data provided by the Resource Data Division (RDD) of the Alberta Department of Sustainable Development. The digital elevation data used has a 100 m resolution. Ground control points (GCPs) are collected from 1:20 000 Alberta Access Vectors and an Alberta mosaic of orthorectified Indian remote sensing satellite (IRS) images, which are also provided by RDD. An average GCP root mean-square error of 20 m is obtained. The image file is in ER Mapper format and projected to UTM zone 11 or 12 with a datum of NAD83. The data remain in unsigned, 16-bit integer format, and the pixel size remains at 12.5 m. Figure 6 is an example of the orthorectified images used for tiling the NTS 84E dataset.




Figure 6. One of the orthorectified scene images used for tiling the NTS 84E dataset: scene MO200868 of Standard Beam Mode 7 descending.

3.3 Mosaic (Tiling) Process

The orthorectified images are tiled to 25 NTS map areas of Standard Beam Mode S1/S7 ascending/descending. For the S1 mosaics, the near-nadir sides of the images have been favoured in the mosaic process. For the S7 mosaics, the off-nadir sides of the images have been favoured. This maximizes the incidence angle difference between the S1 and S7 mosaics. Radiometric differences between adjacent images are minimized using two-dimensional, piecewise linear gain and offset adjustment functions, which are interactively adjusted to achieve an optimum balance. The balanced mosaics are then clipped to 1:250 000 NTS tiles. The NTS tile image file is in ER Mapper format and projected to UTM zone 11 or 12 with a datum of NAD83. The data are converted into unsigned, 8-bit integer format, and the pixel size remains at 12.5 m. Figure 7 is a pseudocolour composite of the orthorectified and tiled NTS 84E image dataset.




Figure 7. Pseudocolour composite of orthorectified NTS 84E image dataset of Standard Beam Mode S1/S7 ascending/descending beam positions (RGB=S7d, S7a, S1d).

3.4 Principal Component Analysis

NTS images of four beam positions (S1 ascending/descending and S7 ascending/descending) for the same NTS map area are used as input channels for principal component analysis (PCA). This results in 25 PCA image datasets; each contains four layers for the PC1, PC2, PC3 and PC4 images for the same NTS map area. During the PCA, the S7 ascending image is used to mask the lakes so as to remove the lakes from the calculation of the covariance eigenvectors. The S1 ascending image is multiplied by 1.35, and the S1 descending image is multiplied by 1.60 so as to match the means of the S1 and S7 ascending/descending images. The covariance eigenvectors are determined using a 10 000 columns by 20 000 rows window of the four beam mode images. The window is located between UTM zone 12 NAD 83 coordinates 339313 E to 464319 E and 6414500 N to 6164502 N. An ER Mapper std_dev_1.6 filter is applied to each of the four beam position images. After PCA, a value of 11 000 was added to PC3 values and 5 000 to PC4 values to bring all of the image values into the positive range. The resultant image dataset is in ER Mapper format and projected to UTM zone 11 or 12 with a datum of NAD83. The dataset was converted into unsigned, 8-bit integer format, and the pixel size remains at 12.5 m. Figure 8 is a pseudocolour composite of the principal component dataset for NTS 84E.




Figure 8. Pseudocolour composite of NTS 84E image dataset of principal component PC1, PC2, PC3 and PC4 (RGB=PC2, PC1, PC3).

3.5 Additional Resampled Images and Maps

For a wider scope of users, including non-GIS or inexperienced professionals to use the data, single-band images in GeoTIFF format were created from each band of the orthorectified and PCA image datasets mentioned above. This results in 8 images for each NTS map area. They are: (1) S1 ascending, (2) S1 descending, (3) S7 ascending, (4) S7 descending, (5) PC1, (6) PC2, (7) PC3 and (8) PC4 images. The GeoTIFF images are in the same projection as the orthorectified and PCA image datasets, but have been re-sampled into 27 m pixel size in order to reduce file size. They can be used with other GIS data to generate maps of specific interests to the user.


In addition, simple maps for these images were created. This results in 8 maps for each NTS map area. These maps are included on the two accompanying CDs as Figures 9 to 16. They can be printed or plotted, depending on the users' software and output capability, and each map includes some general tips for interpretation.

4 Conclusion

The image datasets for NTS 84E contain two sets of data: orthorectified RADARSAT-1 image dataset with images of four beam mode positions: S1/S7 beam modes and ascending/descending paths; and principal component image dataset containing images of PC1, PC2, PC3 and PC4, which are derived from the orthorectified image dataset. The imagery is obtained through orthorectification and mosaicking of the RADARSAT-1 path images covering NTS 84E. Additional single-band images in GeoTIFF format were also created. The various image datasets included herein can be used for a wide range of applications, including forestry, land cover classification, soil moisture mapping, hydrology, geomorphology and geology for the NTS 84E map area.

5 References

- Grunsky, E.C. (2002a): Satellite imagery catalogue; Alberta Energy and Utilities Board, EUB/AGS Geo-Note 2002-18, 24 p.
- Grunsky, E.C. (2002b): Northern Alberta mosaic of RADARSAT-1 principal components images derived from S1/S7 ascending/descending imagery; Alberta Energy and Utilities Board, EUB/AGS Geo-Note 2002-24, 13p.
- Grunsky, E.C. (2002c): The application of principal components analysis to multi-beam RADARSAT-1 satellite imagery – a tool for land cover and terrain mapping; Canadian Journal of Remote Sensing, v. 28, no. 6, p. 758-769.
- Paganelli, F., Grunsky, E.C., Richards J.P. and Pryde R. (2003): Use of RADARSAT-1 principal component imagery for structural mapping: a case study in the Buffalo Head Hills area, northern central Alberta, Canada; Canadian Journal of Remote Sensing, v. 29, no. 1, p. 111-140.
- RADARSAT International (RSI) 1997: RADARSAT Geology Handbook, on-line version, 60 p.
- RADARSAT International (RSI) 1999: RADARSAT Illuminated: Your Guide to Products & Services, on-line version, 131 p.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.


As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (65 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1:250 000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to roughness at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., "averaged" across the about 25 m² field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative coverage and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1:250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).


Some general tips for interpreting the Figures 9 to 12 images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.

1. Standing water, when not disturbed by a strong wind, reflects almost all the incident microwave radiation away from the sensor, resulting in a black or dark tone. In contrast, a strong wind would cause patches of lighter tone on the normally dark response from standing water.
2. Standing water under vegetation, such as some wetlands, particularly those covered by grass, moss and relatively few trees, tends to result in a light tone.
3. Slopes facing toward the sensor are usually lighter than slopes facing away from the sensor.
4. Moist soils are usually brighter than dry soils.
5. Forest canopies generally show up with a more coarse texture than grasslands, which reflects their greater variability in surface roughness response. As well, wetlands with areas of grass or moss interspersed with trees (e.g., black spruce) can also show up as a mottled or 'salt-and-pepper' texture.
6. Canopies with higher moisture content reflect radar energy better than those with low water content; hence they appear in a lighter tone.
7. Conifer versus deciduous trees without leaves show different texture and tones under certain combination of beam mode and look direction.
8. Urban buildings, cars, fences, bridges, etc., tend to result in bright signatures.
9. In general, Standard Beam 1 images are more sensitive to soil and vegetation moisture than Standard Beam 7 images. As a result, Standard Beam 1 images tend to show more variation of tones.
10. The same terrain may appear different in tone when imaged at different incident angles and in different look directions, hence the same area may have a differing response depending on the simple map or figure evaluated.

Elevation Map for NTS 84E



Look Directions and Incident Angles of RADARSAT-1 S1 and S7 Ascending/Descending Beam Modes





Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.ag.gov.ab.ca

Geo-Note 2003-24, Figure 9

RADARSAT-1 Standard Beam 1 Ascending Image for Chinchaga River, Alberta (NTS 84E)

Compilation by S. Mei, 2003




Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as PhotoSat). Additional image processing is made by S. Mei, Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.


As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (65 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1:250,000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to roughness at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., 'averaged' across the about 25 m field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative coverage and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1:250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).


Some general tips for interpreting the Figures 9 to 12 images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.

1. Standing water, when not disturbed by a strong wind, reflects almost all the incident microwave radiation away from the sensor, resulting in a black or dark tone. In contrast, a strong wind would cause patches of lighter tone on the normally dark response from standing water.
2. Standing water under vegetation, such as some wetlands, particularly those covered by grass, moss and relatively few trees, tends to result in a light tone.
3. Slopes facing toward the sensor are usually lighter than slopes facing away from the sensor.
4. Moist soils are usually brighter than dry soils.
5. Forest canopies generally show up with a more coarse texture than grasslands, which reflects their greater variability in surface roughness response. As well, wetlands with areas of grass or moss interspersed with trees (e.g., black spruce) can also show up as a mottled or 'salt-and-pepper' texture.
6. Canopies with higher moisture content reflect radar energy better than those with low water content; hence they appear in a lighter tone.
7. Conifer versus deciduous trees without leaves show different texture and tones under certain combination of beam mode and look direction.
8. Urban buildings, cars, fences, bridges, etc., tend to result in bright signatures.
9. In general, Standard Beam 1 images are more sensitive to soil and vegetation moisture than Standard Beam 7 images. As a result, Standard Beam 1 images tend to show more variation of tones.
10. The same terrain may appear different in tone when imaged at different incident angles and in different look directions, hence the same area may have a differing response depending on the simple map or figure evaluated.

Elevation Map for NTS 84E



Look Directions and Incident Angles of RADARSAT-1 S1 and S7 Ascending/Descending Beam Modes





Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.ag.gov.ab.ca

Geo-Note 2003-24, Figure 10

RADARSAT-1 Standard Beam 1 Descending Image for Chinchaga River, Alberta (NTS 84E)

Compilation by S. Mei, 2003




Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as PhotoSat). Additional image processing is made by S. Mei, Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.


As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (65 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1:250 000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to roughness at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., 'averaged' across the about 25 m² field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative coverage and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1:250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).


Some general tips for interpreting the Figures 9 to 12 images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.

1. Standing water, when not disturbed by a strong wind, reflects almost all the incident microwave radiation away from the sensor, resulting in a black or dark tone. In contrast, a strong wind would cause patches of lighter tone on the normally dark response from standing water.
2. Standing water under vegetation, such as some wetlands, particularly those covered by grass, moss and relatively few trees, tends to result in a light tone.
3. Slopes facing toward the sensor are usually lighter than slopes facing away from the sensor.
4. Moist soils are usually brighter than dry soils.
5. Forest canopies generally show up with a more coarse texture than grasslands, which reflects their greater variability in surface roughness response. As well, wetlands with areas of grass or moss interspersed with trees (e.g., black spruce) can also show up as a mottled or 'salt-and-pepper' texture.
6. Canopies with higher moisture content reflect radar energy better than those with low water content; hence they appear in a lighter tone.
7. Conifer versus deciduous trees without leaves show different texture and tones under certain combination of beam mode and look direction.
8. Urban buildings, cars, fences, bridges, etc., tend to result in bright signatures.
9. In general, Standard Beam 1 images are more sensitive to soil and vegetation moisture than Standard Beam 7 images. As a result, Standard Beam 1 images tend to show more variation of tones.
10. The same terrain may appear different in tone when imaged at different incident angles and in different look directions, hence the same area may have a differing response depending on the simple map or figure evaluated.

Elevation Map for NTS 84E



Look Directions and Incident Angles of RADARSAT-1 S1 and S7 Ascending/Descending Beam Modes





Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.ag.gov.ab.ca

Geo-Note 2003-24, Figure 11

RADARSAT-1 Standard Beam 7 Ascending Image for Chinchaga River, Alberta (NTS 84E)

Compilation by S. Mei, 2003




Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as PhotoSat). Additional image processing is made by S. Mei, Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.


As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (65 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1:250 000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to roughness at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., averaged across the about 25 m² field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative coverage and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1:250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).


Some general tips for interpreting the Figures 9 to 12 images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.

1. Standing water, when not disturbed by a strong wind, reflects almost all the incident microwave radiation away from the sensor, resulting in a black or dark tone. In contrast, a strong wind would cause patches of lighter tone on the normally dark response from standing water.
2. Standing water under vegetation, such as some wetlands, particularly those covered by grass, moss and relatively few trees, tends to result in a light tone.
3. Slopes facing toward the sensor are usually lighter than slopes facing away from the sensor.
4. Moist soils are usually brighter than dry soils.
5. Forest canopies generally show up with a more coarse texture than grasslands, which reflects their greater variability in surface roughness response. As well, wetlands with areas of grass or moss interspersed with trees (e.g., black spruce) can also show up as a mottled or 'salt-and-pepper' texture.
6. Canopies with higher moisture content reflect radar energy better than those with low water content; hence they appear in a lighter tone.
7. Conifer versus deciduous trees without leaves show different texture and tones under certain combination of beam mode and look direction.
8. Urban buildings, cars, fences, bridges, etc., tend to result in bright signatures.
9. In general, Standard Beam 1 images are more sensitive to soil and vegetation moisture than Standard Beam 7 images. As a result, Standard Beam 1 images tend to show more variation of tones.
10. The same terrain may appear different in tone when imaged at different incident angles and in different look directions, hence the same area may have a differing response depending on the simple map or figure evaluated.

Elevation Map for NTS 84E





Look Directions and Incident Angles of RADARSAT-1 S1 and S7 Ascending/Descending Beam Modes



Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.ag.gov.ab.ca

Geo-Note 2003-24, Figure 12
RADARSAT-1 Standard Beam 7 Descending Image for Chinchaga River, Alberta (NTS 84E)

Compilation by S. Mei, 2003




Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as Photosat). Additional image processing is made by S. Mei, Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.

As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (65 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1:250,000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to 'roughness' at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., 'averaged' across the about 25 m field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative coverage and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1:250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).

Having said this, some general tips for interpreting the Figures 13 to 16 PCA images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.



The First Principal Component (PC1) image (Figure 13) shows a range of brightness and texture that highlights features associated with differences in vegetation type and density. Areas of closed Aspen, closed Pine, open deciduous vegetation, grasslands and exposed soil appear to have a brighter tone with variable texture. Areas of open black spruce tend to show up as mid tone to dark grey. Shrubby and grassy wetlands also appear as dark areas. In general, darker tones tend to reflect areas of increased moisture (e.g., wetlands and areas of black spruce), whereas lighter tones reflect areas of drier conditions (e.g., better drainage with pine, aspen or exposed soil).

The Second Principal Component (PC2) image (Figure 14) provides information about the degree of land cover type and vegetation density. For example, well-forested lands show up as darker tones, whereas areas of burn and grassy or barren lands show up as lighter tones. Further, open black spruce forest is characterized by darker tones; closed pine forest is displayed in mid-range tones, and areas of dunes and exposed soil show up as the lightest tones. Finally, areas dominated by grass or little vegetation or of burned forest, show up as light- to medium-grey tones.

The Third Principal Component (PC3) image (Figure 15) highlights 'surface roughness'; hence it reflects topographic effects and surface texture of the ground or vegetation canopy. In fact, the discrimination of topographic features using the PC3 image is superior to any other optical commercial satellite imagery, with similar spatial resolution. As a result, areas of drumlins, sand dunes, eskers, embankments and other prominent topographic features typically are more clearly shown on PC3 images than on the other PCA images. Further, areas of outwash, dune fields, stream alluvium and ice contact deposits usually exhibit unique textural characteristics, which can act to assist in the preliminary mapping or differentiation of surficial materials.

The Fourth Principal Component (PC4) image (Figure 16) shows some added differences in vegetation surface and volume scattering response that are not noted from the other three PCA images. Interestingly, open black spruce forest usually appears to display a lighter tone on PC4 images. Such differences on PC4 may reflect a combination of vegetation density and morphology.

Elevation Map for NTS 84E



Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.ag.gov.ab.ca

Geo-Note 2003-24, Figure 13


**RADARSAT-1 Principal Component 1 Image
for Chinchaga River, Alberta (NTS 84E)**

Compilation by S. Mei, 2003

Scale 1:250 000



Projection: Universal Transverse Mercator, Zone 11
Datum: North American Datum, 1983




Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as PhotoSat). Additional image processing is made by S. Mei. Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.

As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (66 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1:250,000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to 'roughness' at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., 'averaged' across the about 25 m field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative cover and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1:250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).

Having said this, some general tips for interpreting the Figures 13 to 16 PCA images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.



The First Principal Component (PC1) image (Figure 13) shows a range of brightness and texture that highlights features associated with differences in vegetation type and density. Areas of closed Aspen, closed Pine, open deciduous vegetation, grasslands and exposed soil appear to have a brighter tone with variable texture. Areas of open black spruce tend to show up as mid tone to dark grey. Shrubby and grassy wetlands also appear as dark areas. In general, darker tones tend to reflect areas of increased moisture (e.g., wetlands and areas of black spruce), whereas lighter tones reflect areas of drier conditions (e.g., better drainage with pine, aspen or exposed soil).

The Second Principal Component (PC2) image (Figure 14) provides information about the degree of land cover type and vegetation density. For example, well-forested lands show up as darker tones, whereas areas of burn and grassy or barren lands show up as lighter tones. Further, open black spruce forest is characterized by darker tones; closed pine forest is displayed in mid-range tones, and areas of dunes and exposed soil show up as the lightest tones. Finally, areas dominated by grass or little vegetation or of burned forest, show up as light- to medium-grey tones.


The Third Principal Component (PC3) image (Figure 15) highlights 'surface roughness'; hence it reflects topographic effects and surface texture of the ground or vegetation canopy. In fact, the discrimination of topographic features using the PC3 image is superior to any other optical commercial satellite imagery, with similar spatial resolution. As a result, areas of drumlins, sand dunes, eskers, embankments and other prominent topographic features typically are more clearly shown on PC3 images than on the other PCA images. Further, areas of outwash, dune fields, stream alluvium and ice contact deposits usually exhibit unique textural characteristics, which can act to assist in the preliminary mapping or differentiation of surficial materials.

The Fourth Principal Component (PC4) image (Figure 16) shows some added differences in vegetation surface and volume scattering response that are not noted from the other three PCA images. Interestingly, open black spruce forest usually appears to display a lighter tone on PC4 images. Such differences on PCA may reflect a combination of vegetation density and morphology.

Elevation Map for NTS 84E



Look Directions and Incident Angles of RADARSAT-1 S1 and S7 Ascending/Descending Beam Modes





Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.ags.gov.ab.ca

Geo-Note 2003-24, Figure 14

RADARSAT-1 Principal Component 2 Image for Chinchaga River, Alberta (NTS 84E)

Compilation by S. Mei, 2003




Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as PhotoSat). Additional image processing is made by S. Mei, Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.

As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (65 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1:250,000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to 'roughness' at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., 'averaged' across the about 25 m field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative coverage and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1:250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).

Having said this, some general tips for interpreting the Figures 13 to 16 PCA images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.



The First Principal Component (PC1) image (Figure 13) shows a range of brightness and texture that highlights features associated with differences in vegetation type and density. Areas of closed Aspen, closed Pine, open deciduous vegetation, grasslands and exposed soil appear to have a brighter tone with variable texture. Areas of open black spruce tend to show up as mid tone to dark grey. Shrubby and grassy wetlands also appear as dark areas. In general, darker tones tend to reflect areas of increased moisture (e.g., wetlands and areas of black spruce), whereas lighter tones reflect areas of drier conditions (e.g., better drainage with pine, aspen or exposed soil).

The Second Principal Component (PC2) image (Figure 14) provides information about the degree of land cover type and vegetation density. For example, well-forested lands show up as darker tones, whereas areas of burn and grassy or barren lands show up as lighter tones. Further, open black spruce forest is characterized by darker tones; closed pine forest is displayed in mid-range tones, and areas of dunes and exposed soil show up as the lightest tones. Finally, areas dominated by grass or little vegetation or of burned forest, show up as light- to medium-grey tones.

The Third Principal Component (PC3) image (Figure 15) highlights 'surface roughness'; hence it reflects topographic effects and surface texture of the ground or vegetation canopy. In fact, the discrimination of topographic features using the PC3 image is superior to any other optical commercial satellite imagery, with similar spatial resolution. As a result, areas of drumlins, sand dunes, eskers, embankments and other prominent topographic features typically are more clearly shown on PC3 images than on the other PCA images. Further, areas of outwash, dune fields, stream alluvium and ice contact deposits usually exhibit unique textural characteristics, which can act to assist in the preliminary mapping or differentiation of surficial materials.

The Fourth Principal Component (PC4) image (Figure 16) shows some added differences in vegetation surface and volume scattering response that are not noted from the other three PCA images. Interestingly, open black spruce forest usually appears to display a lighter tone on PC4 images. Such differences on PC4 may reflect a combination of vegetation density and morphology.

Elevation Map for NTS 84E




Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.aggs.gov.ab.ca

Geo-Note 2003-24, Figure 15


**RADARSAT-1 Principal Component 3 Image
for Chinchaga River, Alberta (NTS 84E)**

Compilation by S. Mei, 2003

Scale 1:250 000



Projection: Universal Transverse Mercator, Zone 11
Datum: North American Datum, 1983




Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as PhotoSat). Additional image processing is made by S. Mei. Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.



Introduction

The RADARSAT-1 satellite, launched by Canada in 1995, is an active, microwave-based sensor that sends its own microwave signals down to the Earth and processes the signals that it receives back. It differs from optical sensors, such as LANDSAT, SPOT and IRS, which collect data at visible and infrared frequencies and rely on reflected sunlight from the Earth. In addition, RADARSAT-1 employs variable beam modes (i.e., differing incidence angles, scene coverage and resolutions) and look directions (i.e., ascending or east looking and descending or west looking), hence the opportunity exists for acquiring a number of separate radar signals, which then can either be evaluated individually or combined statistically in various ways to produce additional information. The quality of the radar backscatter signal is directly related to ground topography, dielectric properties and surface roughness of the terrain being imaged. As a result, RADARSAT-1 images are well suited for mapping geological structure, geomorphology and the moisture content of vegetation or sediment surface materials to a very shallow depth.

As part of their regional mapping strategy, the Alberta Geological Survey acquired RADARSAT-1 images over northern Alberta (north of 55 degrees north latitude) with the following four beam positions: Standard Beam 1 (S1) ascending (71 scenes), S1 descending (70 scenes), Standard Beam 7 (S7) ascending (65 scenes) and S7 descending (68 scenes). The resolution of each of these datasets is about 25 m (that is, the resulting radar responses reflect or encompass a square cell that is areally about 25 m on each side). The strategy of acquiring S1 and S7 imagery was done to contrast the radar responses based on two incidence angles and two look directions. The images were obtained in a dry autumn (September to December 1999) and, thus, provided ideal conditions of no to little deciduous foliage or snow. The acquired scene images were individually orthorectified and then tiled into 25, 1,250,000 scale NTS map areas that cover all of northern Alberta north of latitude 55°N. This results in four RADARSAT-1 images from the four beam positions for each NTS map area (Figures 9 to 12). As well, the four Radarsat image datasets (i.e., S1A, S1D, S7A and S7D) for each NTS map area were processed using Principal Component Analysis (PCA). PCA is a statistical method that evaluates correlation among the signals from the S1A, S1D, S7A and S7D image data, and generates resultant principal component images for each NTS map area. The first four principal components for each NTS map area were then used to produce four simple PCA maps (Figures 13 to 16).

As noted above, radar backscatter is affected by vegetation type, moisture and surface roughness. It is also dependent on the incidence angle and look direction of the radar beam. With respect to vegetation, much of northern Alberta is covered by boreal forest, but there also exist farm lands, wetlands and some other settings with differing vegetation types. With respect to moisture, the response differs markedly for lakes versus land, but the radar moisture signal on land is complex because it reflects varying moisture content in both the vegetation and surface soils. With respect to surface roughness, this also is a complex response, but refers to 'roughness' at the centimetre scale, and results from a combination of both the roughness of the vegetation canopy and of the underlying ground surface terrain (i.e., 'averaged' across the about 25 m field). As a result, surface roughness is related to the nature of the underlying geomorphology, the surficial geology and soil type, and the vegetation type, extent of vegetative coverage and canopy configuration. In turn, these factors also influence the amount of moisture in the soil, and the type of vegetation that is typically associated with the soil. As well, Principal Component Analysis of the RADARSAT-1 imagery acts to add more complexity to the interpretation process. Finally, because each tiled 1,250,000 scale map area image is a composite, usually of a few individual orthorectified RADARSAT-1 images, there can be in places a seemingly abrupt change in tone or texture; these normally occur across a linear or curvilinear boundary that reflects the join of the images. Therefore, because of these complicated interactions between the radar energy and the vegetation, moisture and surface roughness, it is difficult to provide unique interpretation methods for the eight 'simple maps' of RADARSAT-1 imagery (Figures 9 to 16) or PCA imagery (Figures 13 to 16).

Having said this, some general tips for interpreting the Figures 13 to 16 PCA images are provided below, but these are generalizations and intended only for assisting less experienced users to browse the image or evaluate variations on the printed map.


The First Principal Component (PC1) image (Figure 13) shows a range of brightness and texture that highlights features associated with differences in vegetation type and density. Areas of closed Aspen, closed Pine, open deciduous vegetation, grasslands and exposed soil appear to have a brighter tone with variable texture. Areas of open black spruce tend to show up as mid tone to dark grey. Shrubby and grassy wetlands also appear as dark areas. In general, darker tones tend to reflect areas of increased moisture (e.g., wetlands and areas of black spruce), whereas lighter tones reflect areas of drier conditions (e.g., better drainage with pine, aspen or exposed soil).

The Second Principal Component (PC2) image (Figure 14) provides information about the degree of land cover type and vegetation density. For example, well-forested lands show up as darker tones, whereas areas of burn and grassy or barren lands show up as lighter tones. Further, open black spruce forest is characterized by darker tones; closed pine forest is displayed in mid-range tones, and areas of dunes and exposed soil show up as the lightest tones. Finally, areas dominated by grass or little vegetation or of burned forest, show up as light- to medium-grey tones.


The Third Principal Component (PC3) image (Figure 15) highlights 'surface roughness'; hence it reflects topographic effects and surface texture of the ground or vegetation canopy. In fact, the discrimination of topographic features using the PC3 image is superior to any other optical commercial satellite imagery, with similar spatial resolution. As a result, areas of drumlins, sand dunes, eskers, embankments and other prominent topographic features typically are more clearly shown on PC3 images than on the other PCA images. Further, areas of outwash, dune fields, stream alluvium and ice contact deposits usually exhibit unique textural characteristics, which can act to assist in the preliminary mapping or differentiation of surficial materials.

The Fourth Principal Component (PC4) image (Figure 16) shows some added differences in vegetation surface and volume scattering response that are not noted from the other three PCA images. Interestingly, open black spruce forest usually appears to display a lighter tone on PC4 images. Such differences on PC4 may reflect a combination of vegetation density and morphology.

Elevation Map for NTS 84E



Look Directions and Incident Angles of RADARSAT-1 S1 and S7 Ascending/Descending Beam Modes





Published 2003
Copies of this map may be obtained from:
Information Sales
Alberta Geological Survey
Telephone: (780) 422-3767
Web site: www.aggs.gov.ab.ca

Geo-Note 2003-24, Figure 16

RADARSAT-1 Principal Component 4 Image for Chinchaga River, Alberta (NTS 84E)

Compilation by S. Mei, 2003



Acknowledgements:

Digital cartography is made by N.L. Blundon and S. Mei. The RADARSAT-1 principal component images are processed by RGI Resources GIS and Imaging (now renamed as PhotoSat). Additional image processing is made by S. Mei. Reg Olson and Rick Richardson are thanked for beneficial and constructive review.

Disclaimer:

The Alberta Geological Survey and its employees and contractors make no warranty, guarantee or representation, express or implied, or assume any legal liability regarding the correctness, accuracy, completeness, or reliability of this publication. When using information from this publication in other publications or presentations, due acknowledgement should be given to the Alberta Energy and Utilities Board/Alberta Geological Survey.