

Transverse Mercator Projection

Projection transverse de Mercator

DEPOSIT CHARACTERISTICS **GENERAL COMMENTS**

Deposit Number	Material Description	Rese (1000 Gravel) m³)	Additional Comments	Gravel	Fexture (%) Sand	Fines	(%) Wear	Overburden Thickness (m)	Deposit Thickness (m)	Deposit Area (ha)	Deposit Genesis	Additional Comments
1	Fine sand		64	Sand dune area. Reserve estimation based on 2 m depth.						2.0 (assumed)	8	Eolian	Dunes cover 40% of the area.
2	Fine sand		1770	Sand dune area. Reserve estimation based on 2 m depth.					e	2.0 (assumed)	590	Eolian	Dunes cover 15% of the area.
3	Fine sand		680	Sand dune area. Reserve estimation based on 2 m depth.					-	2.0 (assumed)	170	Eolian	Dunes cover 20% of the area.
4	Fine sand	8	44	Sand dune area. Reserve estimation based on 2 m depth.					-	2.0 (assumed)	22	Eolian	Dunes cover 10% of the area.
5	Fine sand		72	Sand dune area. Reserve estimation based on 2 m depth.		1-				2.0 (assumed)	9	Eolian	Dunes cover 40% of the area.
6	Fine sand		14	Sand dune area. Reserve estimation based on 2 m depth.					-	2.0 (assumed)	7	Eolian	Dunes cover 10% of the area.
7	Fine sand	,	152	Sand dune area. Reserve estimation based on 2 m depth.						2.0 (assumed)	19	Eolian	Dunes cover 40% of the area.
8	?		=	Probably sand.					-		475	Fluvial	No information available.
9	Very dirty sandy gravel	27 (sand and	10000	Reserve estimation based on 2 m depth.	50	25	25		-	2.0 (assumed)	135	Glaciofluvial	Rock types - quartzite, soft sandstone, ironstones, shales. Texture figures are estimates from few observations.
10	Fine sand		88	Sand dune area. Reserve esti- mation based on 2 m depth.		7			-	2.0 (assumed)	11	Eolian	Dunes cover 40% of the area.
11	Fine sand		·-		1				-	?	15	Glaciofluvial	No information available.
12	Fine sand	-	510	Sand dune area. Reserve esti- mation based on 2 m depth.					:=	2.0 (assumed)	85	Eolian	Dunes cover 30% of the area.
13	Fine sand		315	Sand dune area. Reserve esti- mation based on 2 m depth.					-	2.0 (assumed)	63	Eolian	Dunes cover 25% of the area.
14	?	-		Probably sand.						?	3	Glaciofluvial	No information available.
15	?	-	-	Probably sand.			le:			?	7	Glaciofluvial	No information available.
16	?	-	-	Potential prospect.					-	?	44	Fluvial	No information available.

Deposit Number — Granular deposits shown on this map may have commercial possibilities. That assumption followed from two criteria used in the mapping process: study of the area considered only granular deposits greater than one metre thick, and covering an area more than one hectare; and it only considered deposits where the mineral-aggregate thickness was greater than the overburden thickness. Although the scale of mapping did not permit investigation of all small deposits, many small deposits containing existing pits are indicated.

Material Description — Sand and gravel has a variety of applications, such as concrete for construction, asphalt concrete, subbase and base course aggregate for roads, gravel and sand for road surfaces, and pit run for fill. Gradation, rock hardness, and binding characteristics, are some of the specific qualities that are considered in aggregate towards determining its end use. This map indicates these, and other, geological qualities of the sand and gravel within each deposit, but does not indicate their potential uses. The terms used in the table are defined in the figure below.

Reserves — The method of calculating in cubic metres the aggregate reserves of deposits took four basic steps. First, the area, in hectares, of each deposit was determined using aerial photographs. Second, geological interpretation, sometimes supported by subsurface information, was assumed in determining the geometry of each deposit, to estimate an overall, average deposit thickness in metres. Third, geological study and limited sample analyses determined the texture (gradation) of sediments in the deposit, and an overall average percentage of gravel and sand. Finally, the volume was calculated as follows: reserve gravel (m³) = area (ha) × thickness (m) × 10,000 × % gravel; the same formula was used for sand.

Texture — The texture of the sediment refers to the percentage of particles of various sizes. For mineral aggregate, the most important fractions are the gravel and sand. The actual dimensions of the clasts and particles in these fractions are given in the figure. The values given for a particular deposit were determined from a field estimate, or from laboratory analysis, of one or more samples from that deposit. Where more than one sample is taken the tabulated number is the mean value.


Wear — The resistance of gravel-size clasts to wear or abrasion can be measured in a laboratory test (ASTM-C131, Los Angeles Abrasion Testing). The amount of material that breaks down into smaller sizes is measured and related to the original sample weight in terms of percent wear. The higher the percentage wear the more susceptible the gravel is to breakdown under stress. Gravel with a percentage wear of less than 40 is considered very resistant.


Overburden Thickness — The thickness of non-economic material, or overburden, covering a deposit, sometimes is a limiting factor in the exploitation of an aggregate deposit. The tabulated values given are approximate overburden thicknesses as determined from geological investi-

Deposit Area — Deposits in this study were delineated by interpretation of aerial photographs and the contacts should be considered approximate. Information is precise only where test holes, or

geological sections, are indicated.

Deposit Genesis — The genesis, or formation, of deposits is vital to the understanding of the gradational nature, extent and geometry of the deposit. This understanding forms the basis for extrapolation from a limited number of known points (test holes, pits, sections) and permits an





Assumed boundary

Active or inactive pit Alberta Geological Survey test hole ▲ Sand or gravel exposure

Buried sand or Gravel deposit

Aggregate Resources

83F/8 Moose Creek

Geology and compilation 1986. Additional information from M.A. Roed, 1970.

This is a sand and gravel resource map prepared by the Alberta Geological Survey as part of a series at a scale of 1:50,000. The series represents an ongoing aggregate inventory of Alberta which provides data for general land-use planning, land management or aggregate exploration. Please note that the delineation of deposits and calculation of reserves are approximations only. Alberta Energy and Natural Resources provides financial support for the Aggregate Inventory.

Cartography by Alberta Research Council, Graphic Services, J.K. Matthie.

